

ES30



Audio para el hogar

Calificación: Sin calificación
[Haga una pregunta sobre el producto](#)

Descripción

oidos AUDIO E ILUMINACIÓN PROFESIONAL			
	ES10	ES20	ES30
Frequency Response (±3dB)	60Hz - 40kHz	60Hz - 40kHz	50Hz - 40kHz
Max. Recommended Amplifier Power*	100W	125W	125W
Power Handling (Continuous/Peak)	50W/200W	60W/240W	70W/280W
Sensitivity (2.83V/1m)	86dB	86dB	86dB
Nominal Impedance	8 Ohms	8 Ohms	8 Ohms
Crossover Frequencies	2000Hz - 24dB/octave; 9000Hz - 18dB/octave	2000Hz - 24dB/octave; 12,000Hz - 18dB/octave	3000Hz - 24dB/octave; 9000Hz - 18dB/octave
Low-Frequency Transducer	4" (100mm) PolyPlus™ shielded	5" (125mm) PolyPlus™ shielded	6" (150mm) PolyPlus™ shielded
High-Frequency Transducer	3/4" (19mm) Titanium-laminated dome, shielded; EOS waveguide	3/4" (19mm) Titanium-laminated dome, shielded; EOS waveguide	3/4" (19mm) Titanium-laminated dome, shielded; EOS waveguide
Ultrahigh-Frequency Transducer	3/4" (19mm) Polyester-film ring-radiator, shielded; EOS waveguide	3/4" (19mm) Polyester-film ring-radiator, shielded; EOS waveguide	3/4" (19mm) Polyester-film ring-radiator, shielded; EOS waveguide
Dimensions With Grille (H x W x D)	7.76" x 12" x 6.51" (201mm x 305mm x 140mm)	10.12" x 6.78" x 6" (258mm x 174mm x 203mm)	15.34" x 9.24" x 12" (391mm x 235mm x 305mm)
Weight per Speaker	8.8 lb (4kg)	10.3 lb (4.6kg)	16.6 lb (8.0kg)

oidos AUDIO E ILUMINACIÓN PROFESIONAL			
	ES80	ES90	ES26C
Frequency Response (±3dB)	45Hz - 40kHz	30Hz - 40kHz	80Hz - 40kHz
Max. Recommended Amplifier Power*	200W	225W	125W
Power Handling (Continuous/Peak)	100W/400W	110W/440W	75W/300W
Sensitivity (2.83V/1m)	90dB	91dB	90dB
Nominal Impedance	8 Ohms	8 Ohms	8 Ohms
Crossover Frequencies	700Hz, 3000Hz - 24dB/octave; 12,000Hz - 18dB/octave	500Hz, 3000Hz - 24dB/octave; 12,000Hz - 18dB/octave	3000Hz - 24dB/octave; 12,000Hz - 18dB/octave
Low-Frequency Transducers	Dual 6" (150mm) PolyPlus™ shielded	Dual 6" (150mm) PolyPlus™ shielded	Dual 5" (125mm) PolyPlus™ shielded
Mid-Range Transducer	4" (100mm) PolyPlus™ shielded	4" (100mm) PolyPlus™ shielded	NA
High-Frequency Transducer	3/4" (19mm) Titanium-laminated dome, shielded; EOS waveguide	3/4" (19mm) Titanium-laminated dome, shielded; EOS waveguide	3/4" (19mm) Titanium-laminated dome, shielded; EOS waveguide
Ultrahigh-Frequency Transducer	3/4" (19mm) Polyester-film ring-radiator, shielded; EOS waveguide	3/4" (19mm) Polyester-film ring-radiator, shielded; EOS waveguide	3/4" (19mm) Polyester-film ring-radiator, shielded; EOS waveguide
Dimensions With Grille (H x W x D)	42.11/16" x 8.54" x 12" (1081mm x 218mm x 305mm)	42.11/16" x 10.14" x 15.1/8" (1081mm x 258mm x 384mm)	7 x 18.3/4" x 12" (178mm x 470mm x 305mm)
Weight per Speaker	46.2 lb (21kg)	62.4 lb (28.3kg)	16.7 lb (7.6kg)

